

Sharp edge Inertia Reel / Retractable Block

SPECIFICATION FOR 915207 (7m) AND 915210 (10m)



Steel Triple Action Karabiner: made of alloy steel, MBS: 25kN, Gate Opening: 22mm, with golden yellow galvanised finish.



Swivel Eye: The Anchorage eye comes with swivel action, hence prevents any undue twist of the retracted lanyard. While working, or in the event of the fall.



Polymer Casing with carry handle: Casing is made of High Impact Strength Polymer to prevent breakage and is nearly indestructible.



Retractable Steel Wire Rope: 4.5mm diameter, Galvanised, 10 Meter.



Snot for minimizing the accidental Locking: consist of snot which minimizes the accidental locking of the block when the wire rope is released suddenly.



Steel Triple Action Swivel Hook with Load Indicator: made of forged alloy steel with the golden yellow finish, Gate Opening: 21mm, MBS: 25kN. Impact Indicator allows the easy visual inspection to determine if the unit has experienced a fall by a user.

REF.	915207	915210
------	--------	--------

LG.

7.0 m | 10.0 m



MAX 140 KG / 100 KG (OVER A EDGE)

CE / AS/NZS	EN 360:2002 / AS 1891.3:2020 Amd 1:2021 (BMP No. 739186)
-------------	--



Polyamide 6 - 30% fiber Glass

STEEL Ø 4.5 mm

	STEEL ANSI D/A Karabiner / ANSI Triplock Karabiner with fall indicator
--	--



x2

MBS	15 kN
-----	-------



YES

	3.08 KG 4.28 KG
--	-------------------

 Length Max. user weight	 Number of swivels	 Material of casing / wire rope	 Approved for work near sharp edges	 Material of top connector / bottom connector
-----------------------------	-----------------------	------------------------------------	--	--