

Kernmantle Pole Strap - Double Action Snap Hook with Steel Triple Locking Karabiner

SPECIFICATION FOR 916240



Double Action Snap Hook: made of forged alloy steel, MBS 23kN. Gate opening 20mm, with golden yellow galvanised finish. ANSIZ359.12-2009 - 16kN gate









Triple Action Locking Karabiner: made of alloy steel, MBS 40kN. Gate opening 21.5mm, with golden yellow galvanised finish. ANSIZ359.12-2009 - 16kN gate



Alloy Rope Adjuster: manually locks onto kernmantle rope, made of Aluminum alloy, MBS 15kN, Silver anodized finish. - EN 358



Plastic Rope Thimble: prevents the rope from being damaged by metallic contact or abrasion from the webbing

REF.	916240		
AS/NZS	AS 1891.5:2020		
	Number of users	X 1	
	Max user weight	140 kg's	
LG	Adjustable Length 1 m - 2.5 m		
MAT.	Kernmantle Rope - diameter 12mm		
R (kN) / MFD	12 kN / ≤ 600mm		
	AUSTLIFT YAG001 - EN 358 		
	PN 145 - ANSI Z359.12-2009		PN114A (C) - ANSI Z359.12-2009
	1.2 KG		

		R (kN)	/	MFD
Rope / Webbing Adjuster	Harness connector	Static strength (Static load applied to pole strap)	/	Maximum Fall Distance (Maximum distance allowed to fall on pole strap as per AS/NZS 1891.4 guidelines)